

We claim:

1. A cleaning article having a sheet configuration comprising a flexible substrate having a first portion, divided by an impermeable
5 barrier extending through the flexible substrate from a second portion, wherein the first portion contains a cleaning composition, and the second portion is essentially dry, wherein the cleaning composition comprises (preferably consists essentially of):

(a) 0.01-10%wt. of one or more surfactants selected from
10 anionic surfactants, nonionic surfactants, cationic surfactants, amphoteric surfactants and mixtures thereof;

(b) 0 - 40%wt. of a scouring agent selected from the group consisting of oxides, carbonates, quartzes, siliceous chalk, diatomaceous earth, colloidal silicon dioxide, alkali
15 metasilicates, organic abrasive materials selected from polyolefins, polyethylenes, polypropylenes, polyesters, polystyrenes, acetonitrile-butadiene-styrene resins, melamines, polycarbonates, phenolic resins, epoxies and polyurethanes, abrasive water soluble salts, natural materials
20 selected from rice hulls, corn cobs, and the like, nepheline syenite, or talc and mixtures thereof;

(c) 0 - 10%wt. of a thickener;

(d) 0 - 10%wt. of one or more organic solvents;

(e) 0 - 7%wt. of an organopolysiloxane;

25 (f) 0 - 3%wt. of an acid;

(g) 0 - 5%wt. of one or more optional constituents;

(i) to 100%wt. of water,

wherein the barrier prevents migration of the cleaning composition from the first portion of the cleaning article to the second portion
30 of the cleaning article.

2. The cleaning article of claim 1 wherein the cleaning composition comprises an organopolysiloxane.

35 3. The cleaning article of claim 1 wherein the cleaning composition comprises an acid.

4. The cleaning article according to any of claims 1 - 3 wherein the cleaning composition comprises both an anionic and a nonionic surfactant.
- 5 5. The cleaning article according to any of claims 1 - 3 wherein the cleaning composition comprises 2-35%wt. of a scouring agent.
6. The cleaning article according to any of claims 1 - 3 wherein
10 the cleaning composition comprises 0.01-5%wt of a thickening agent.
7. The cleaning article according to any of claims 1 - 3 wherein the cleaning composition comprises 0.01-7%wt. of an organic solvent.
- 15 8. A method for the treatment of surfaces, particularly vitroc ceramic surfaces which method comprises the steps of:
providing a cleaning article according to any of the preceding claims;
applying the first portion of the cleaning article to a soiled
20 surface, especially a vitroc ceramic surface;
manually spreading the cleaning product and cleaning the soiled surface;
subsequently removing the first portion of the cleaning article from the surface,
25 applying the second portion of the cleaning article to the surface to manually buff the treated surface to provide a shined, cleaned appearance.
9. A cleaning article according to claim 1 wherein the
30 impermeable barrier is a heat sealed strip extending through the flexible substrate or is a layer or strip of a cured resin on the substrate.